



CARAVANRVCAMPING

Parts * Accessories * Appliances * Australia Wide


PH: 1800 RV PARTS

Email: sales@caravanRVcamping.com



Dometic CALR242

Reverse cycle roof top air conditioner



Dometic FreshJet 2200

Roof top air conditioner with heating element



Dometic FreshJet 3200

Reverse cycle roof top air conditioner



Dometic BR342

Reverse cycle roof top air conditioner



Truma Aventa Comfort

Reverse cycle roof top air conditioner



Truma Saphir

Reverse cycle under bunk air conditioner



Aircommand Ibis 3

Reverse cycle roof top air conditioner



| | | | |
|---------------------------------------|------------------|-----------------|-----------------|
| Reference Number | CALR242-ADB-KIT | FJ2200-ADB-KIT | FJ3200-ADB-KIT |
| Best for vehicle length | up to 6.5 m | up to 5 m | up to 7.5 m |
| Electrical Rating | 230 volts | 230 volts | 230 volts |
| Nominal (compressor capacity) | 3.0 kW | 2.2 kW | 3.0 kW |
| Cooling Capacity (ISO5151) | 2.3 kW | 1.8 kW | 2.6 kW |
| Heating Capacity | 2.1 kW | 1.2 kW | 2.4 kW |
| Current Draw (Cooling/Heating) | 5.8 A / 5.5 A | 4.1 A / 5.2 A | 6.3 A / 5.5 A |
| Operating Temperature Range | -7 to 43°C** | 0 to 52°C | 0 to 52°C |
| Airflow (high fan) | 282 m³/h | 330 m³/h | 400 m³/h |
| Dimensions (W x H x L mm) | | | |
| External | 736 x 255 x 1027 | 562 x 225 x 787 | 650 x 248 x 980 |
| Internal | 635 x 508 x 70 | 535 x 480 x 47 | 535 x 480 x 47 |
| Roof opening (W x D mm) | 360 x 360 | 400 x 400 | 400 x 400 |
| Roof thickness (mm) | 38 -150 (approx) | 25 – 60 | 25 – 60 |
| Weight (kg) | 45 | 32 | 37 |
| Number of blower speeds | 3 | 4 | 4 |
| Remote control | Yes | Yes | Yes |

- | | | |
|--|---|--|
| <p>Features</p> <ul style="list-style-type: none"> → Removable and washable filters → Features four cooling modes, reverse cycle and timer function → Air distribution box with air shower vent, digital readout and status indication LEDs → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) → Quiet operation <p>** Performance is reduced at temperatures under 7°C and over 35°C.</p> | <ul style="list-style-type: none"> → Light weight → Temperature pre-setting (+16°C to +31°C) → Automatic mode → Lighting on/off → Suitable for poptop caravans → Low current draw → Timer function → Built in free ventilation of 650 mm² (can contribute to overall requirement for gas regulations) → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) | <ul style="list-style-type: none"> → Light weight → Temperature pre-setting (+16°C to +31°C) → Automatic mode → Lighting on/off → Quiet operation → Vertical compressor for reduced vibration levels → Timer function → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) |
|--|---|--|

| | | | |
|-----------------|------------------|-----------------|------------------|
| BR342-ADB-KIT | AVENTA MARK2-KIT | SAPHIR R/C-KIT | 8100001 |
| up to 7.5 m | up to 7.5 m | up to 6.5 m | up to 6.5 m |
| 230 volts | 230 - 240 volts | 230 - 240 volts | 240 volts |
| 3.6 kW | | | 3.2 kW |
| 3.0 kW | approx. 2.4 kW | approx. 2.4 kW | 2.7 kW |
| 2.9 kW | approx. 1.7 kW* | approx. 1.7 kW* | 2.4 kW |
| 6.3 A / 5.3 A | 4.2 A / 3.7A | 4.2 A / 3.7 A | 5.7 A / 4.9 A |
| -7 to 43°C# | 4 to 43°C | 4 to 43°C | -5°C Minimum |
| 526m³/h | 400m³/h | 380m³/h | 780 m³/h |
| | | | |
| 721 x 670 x 282 | 1008 x 660 x 248 | N/A | 848 x 222 x 1120 |
| 581 x 530 x 35 | 670 x 523 x 46 | 400 x 290 x 628 | 535 x 32 x 535 |
| 360 x 360 | 400 x 400 | N/A | 360 x 360 |
| 38 - 165 | 25 - 50 *** | N/A | 25 - 85 |
| 40 | 33 | approx 23.5 | 48 |
| 3 | 3 + sleep mode^ | 3 + sleep mode | 3 |
| Yes | Yes | Yes | Yes |

- | | | | |
|---|---|--|--|
| <ul style="list-style-type: none"> → Optional electronic wall control → Condensation drain outlets allow optional attachment of tubing to direct runoff away from doorways/windows → Vertical compressor for reduced vibration → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) <p># Performance is reduced at temperatures under 7 °C and over 35 °C</p> | <ul style="list-style-type: none"> → Aesthetically pleasing → Sleep function for quieter interior cooling → Timer function → Slimmest air distributor on the market → Powerful cooling → Energy saving heating → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) <p>* Heating is not possible at an outside temperature of less than 4 °C</p> <p>*** With additional roof thickness adapters unit can be fitted to roof thickness up to 110mm</p> <p>^ 2 speeds in heating mode</p> | <ul style="list-style-type: none"> → Integrated heat pump function → Highly efficient, delivers exceptionally high performance → Extremely light weight at only 23.5 kg → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) <p>† Heating is not possible at an outside temperature of less than 4 °C</p> <p>Includes 3 air outlets, nuts, 3 ducting clips & air intake vent. Please note: Ducting must be ordered separately</p> | <ul style="list-style-type: none"> → Ultra thin ADB with four outlets → Self-adjusting connecting duct providing a simple 'one click' system to suit a range of roof thicknesses → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) |
|---|---|--|--|





Aircommand Sparrow

Reverse cycle roof top air conditioner



Aircommand Ibis

Reverse cycle under bunk air conditioner



Aircommand Cormorant

Reverse cycle roof top air conditioner



| | | | |
|---------------------------------------|--|---|--|
| Reference Number | 5860001 | 8000002 - white / 8000003 marinised | 5750001 |
| Best for vehicle length | up to 5 m | up to 6.5 m | up to 7 m |
| Electrical Rating | 240 volts | 240 volts | 240 volts |
| Nominal (compressor capacity) | 2.2 kW | 2.8 kW | 3.5 kW |
| Cooling Capacity (ISO5151) | 1.7 kW | 2.4 kW | 2.8 kW |
| Heating Capacity | 1.7 kW | 2.2 kW | 2.6 kW |
| Current Draw (Cooling/Heating) | 4.3 A / 3.8 A | 5.7 A / 5.3 A | 5.5 A / 5.4 A |
| Operating Temperature Range | -5°C Minimum | -5°C Minimum | -5°C Minimum |
| Airflow (high fan) | 319 m³/h | 423 m³/h | 558 m³/h |
| Dimensions (W x H x L mm) | | | |
| External | 560 x 215 x 968 | 845 x 220 x 1040 | 670 x 360 x 985 |
| Internal | 527 x 64 x 550 | 527 x 64 x 550 | 527 x 64 x 550 |
| Roof opening (W x D mm) | 360 x 360* | 360 x 360* | 360 x 360* |
| Roof thickness (mm) | 25 - 90 | 25 - 90 | 25 - 85 |
| Weight (kg) | 31 | 52 | 40 |
| Number of blower speeds | 3 | 3 | 3 |
| Remote control | Yes | Yes | Yes |
| Features | <ul style="list-style-type: none"> → Flip-down electronic LED control panel → Remote control → Low profile rooftop unit → Light weight suitable smaller caravans and poptops → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) | <ul style="list-style-type: none"> → Flip-down electronic LED control panel → Polyurethane construction → Low profile rooftop unit → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) | <ul style="list-style-type: none"> → Flip-down electronic LED control panel → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) |

*Can be fitted to 400 x 400 opening with the use of Euro Adaptor (0035010-Adapter)



Aircommand Sandpiper

Reverse cycle under bunk air conditioner



Aircommand Heron 2.2

Split system air conditioner with heating element



Aircommand Heron Q

Reverse cycle split system air conditioner



Aircommand Jabiru

Reverse cycle all-in-one air conditioner



| | | | |
|---|---|--|---|
| 7000001 | 4270001 - white / 4270002 - silver | 4810001 - white / 481000 - silver | 6100001 |
| up to 5 m | up to 5 m | up to 5 m | up to 5 m |
| 240 volts | 240 volts | 240 volts | 240 volts |
| 2.2 kW | 2.6 kW | 2.6 kW | 2.2 kW |
| 2.0 kW | 2.4 kW | 2.3 kW | 1.5 kW |
| 1.7 kW | 1.5 kW | 2.3 kW | 1.4 kW |
| 4.6 A / 3.8 A | 5.0 A / 6.5 A | 6.1 A / 5.6 A | 4.8A / 4.4A |
| -1°C Minimum | | -5°C Minimum | -5°C Minimum |
| 402 m³/h | 297 m³/h | 335 m³/h | 325 m³/h |
| | | | |
| N/A | 380 x 240 x 250 | 380 x 240 x 250 | N/A |
| 442 x 287 x 692 | 462 x 245 x 450 | 455 x 770 x 295 | 300 x 750 x 565 |
| N/A | N/A | N/A | N/A |
| N/A | N/A | N/A | N/A |
| 31 | 36 | 41 | 44 |
| 3 | 3 cooling, 1 heating | 3 | 3 |
| Yes | No | Yes | Yes |
| <ul style="list-style-type: none"> → Electronic LED control panel → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) <p>Ducting must be ordered separately</p> | <ul style="list-style-type: none"> → Easy to operate knobs to control fan speed, and temperature. → Horizontal and vertical air adjustment → Compact design for greater flexibility with install location → Heron air conditioners must be connected and commissioned by a licensed air conditioning technician → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) | <ul style="list-style-type: none"> → Electronic LED control panel → Horizontal and vertical air adjustment → Easy to install condenser box fitted from outside the van → Heron air conditioners must be connected and commissioned by a licensed air conditioning technician → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) | <ul style="list-style-type: none"> → All-in-one cupboard mount Electronic LED control panel → Compact design for greater flexibility with cupboard installation → Must be installed directly on the floor under benchtop → Will operate on most premium brand inverter type generators (check with your generator supplier for compatibility) |





Dometic Group is a customer-driven, world-leading provider of leisure products for the RV, automotive, truck and marine markets. We supply the industry and aftermarket with a complete range of air conditioners, refrigerators, awnings, cookers, sanitation systems, lighting, mobile power equipment, comfort and safety solutions, windows, doors and other equipment that make life more comfortable away from home.

Dometic Group supplies a wide range of workshop equipment for service and maintenance of built-in air conditioners. Dometic Group also provides specially designed refrigerators for hotel rooms, offices, wine storage and transport and storage of medical products. Our products are sold in almost 100 countries and are produced mainly in wholly-owned production facilities around the world.

AUSTRALIA

Dometic Australia, Queensland 1

1 John Duncan Court
Varsity Lakes QLD 4227
Phone: +61 (0)7 5507 6000
Fax: +61 (0)7 5507 6001

Dometic Australia, Queensland 2

2/129 South Pine Road
Brendale QLD 4500
Phone: +61 (0)7 3205 7599
Fax: +61 (0)7 3881 1409

Dometic Australia, Victoria 1

Bldg 3B, Clayton Business Park
1508 Centre Rd, Clayton VIC 3168
Phone: +61 (0)3 9239 1000
Fax: +61 (0)3 9239 1099

Dometic Australia, Victoria 2

10 Metrolink Circuit
Campbellfield VIC 3061
Phone: +61 (0)3 9239 1000
Fax: +61 (0)3 9303 9084

Dometic Australia, Western Australia

12 Prosperity Ave
Wangara WA 6065
Phone: +61 (0)8 9303 3555
Fax: +61 (0)8 9303 3577

Dometic Australia, South Australia

954 Port Road
Albert Part SA 5014
Phone: +61 (0)8 8345 8444
Fax: +61 (0)8 8243 0628

All Locations

E-mail: sales@dometic.com.au
Web: www.dometic.com.au
Facebook: www.facebook.com/DometicWaecoAustralia

FREECALL: 1800 21 21 21

Your retailer:

Caravan RV Camping

