



The Arana RV Instantaneous Gas Hot Water Heater offers a streamlined and efficient solution for heating water in caravans and RVs.

Say goodbye to the inconvenience of waiting for your hot water tank to warm up, thanks to the Arana Instantaneous Gas Water Heater. Crafted specifically to meet the needs of RV hot water systems, this heater is equipped with an intelligent control system to ensure a consistent supply of heated water.

You have the flexibility to choose your desired water temperature using the provided digital control, with a maximum setting of 51°C.

Rest easy knowing multiple safety features are in place such as overheating, anti-freezing, flame out, dry burn, water overpressure protection all monitored by the intelligent control system, the heater will shut down immediately in case of any malfunction.

FEATURES

- · New smart technology, no preheating required
- Automatic pulse ignition, segmented burners, precise temperature
- 60,000 BTU, up to 9L of hot water per minute
- Strong wind resistance, designed with an anti-wind back device, helping to prevent cold air from entering the heat exchanger
- Frost protection function
- · Auto-diagnosis and fault code display function
- · Black & white doors available
- · ETL / SAI / Watermark / SAA Certified

DESCRIPTION	PART NUMBER
Arana Instantaneous Gas Hot Water Heater Unit	266220002
Hot Water Heater Door - Black	266220000
Hot Water Heater Door - White	266220001



For full specifications and pricing see our website. For trade & wholesale pricing please speak to one of our sales reps.





No preheating, sufficient hot water at any time.

New smart technology, automatic ignition, segmented burners, precise temperature control.

60000BTU, 9 liters of hot water per minute, could fully meet the daily hot water demand for RV life.



Elegant design.

Embedded installation, saving space.

Anti wind back device, strong wind resistance, not afraid of any harsh environment.



Multiple devices to ensure safety.

Overheating protection, antifreezing protection, anti-dry protection, anti-flame protection, pressure relief protection, low noise, Gas Safety and WaterMark certified, safe and worry free.

SPECIFICATIONS

ТҮРЕ	RH09G
GAS TYPE	Universal LPG
NOZZLE QUANTITY	5
NOZZLE DIAMETER	1.1mm
IGNITION METHOD	Automatic
MAXIMUM WORKING LOAD PRESSURE	0.4MPa
MINIMUM WORKING LOAD PRESSURE	0.1MPa
NOMINAL GAS PRESSURE	2.8kPa
POWER SUPPLY	12V DC 3Amp
WATER HEATING CAPACITY	9 L/min
MAXIMUM HEATING TEMPERATURE	51°C
WEIGHT	13.5kg
DIMENSIONS (L×W×H)	371 × 320 × 317mm
FREEZE PROTECTION	Yes







