Mobile living made easy.

DOMETIC

THE POWER TO BE PRESENT

DOMETIC CFX3 SPECIFICATIONS	**DOMETIC CFX3 35** Compressor fridge or freezer	**DOMETIC CFX3 45** Compressor fridge or freezer	**DOMETIC CFX3 55** Compressor fridge or freezer	**DOMETIC CFX3 55IM** Compressor fridge or freezer, ice maker	**DOMETIC CFX3 75DZ** Compressor fridge and freezer	**DOMETIC CFX3 95DZ** Compressor fridge and freezer
Storage capacity (l)	36	46	55	53	75	94
Can count (375ml)	50	67	85	83	113 (68/45)	133 (81/52)
Voltage	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC	12/24 V DC and 100 – 240 V AC
USB charging outlet	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating	5 V / 2 A rating
Power consumption (DC 12 V)	Average current draw x running time. Average 0.98 Ah/h (@12 V, 4˚C set, 32˚C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.03 Ah/h (@12 V, 4˚C set, 32˚C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.10 Ah/h (@12 V, 4˚C set, 32˚C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 1.20 Ah/h (@12 V, 4˚C set, 32˚C ambient, ice maker on/maintenance, Bluetooth on, WiFi off)	Average current draw x running time. Average 3.04 Ah/h (@12 V, 4˚C (large), -15˚C (small), 32˚C ambient, Bluetooth on, WiFi off)	Average current draw x running time. Average 3.57 Ah/h (@12 V, 4˚C (large), -15˚C (small), 32˚C ambient, Bluetooth on, WiFi off)
Temperature range	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)	+10 °C to -22 °C (Minimum setting of -18 °C recommended for normal usage)
Insulation	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness	CFC-free PU foam, generous thickness
System	Dometic Waeco ACV20DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV20DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator	Dometic Waeco ACV25DC compressor with integrated VMSO^3 electronics, low voltage protection, adjustable for leisure and starter battery, AC mains priority circuit, dynamically ventilated condenser, aluminium rollbond evaporator
Material	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet & lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet: steel & polypropylene, Lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel	Cabinet: steel & polypropylene, Lid: polypropylene, Handles: aluminium alloy, Hinges: aluminium alloy & stainless steel
Colour	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey	Body: dark grey; Lid: light grey
Weight (kg)	16.9	18.7	20.4	21.3	27.8	29.8
Dimensions (W x H x D) mm	398 x 407 x 694	398 x 476 x 694	720 x 480 x 455	720 x 480 x 455	892 x 472 x 495	962 x 472 x 530
Quality features	Bluetooth & WiFi enabled, detachable lid, interior light, drain plug, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, detachable lid, interior light, drain plug, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, detachable/ reversible lid, interior light, drain plug, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, ice maker, detachable/ reversible lid, interior light, drain plug, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, dual zone refrigeration or freezing, detachable/reversible lids, interior lights, drain plugs, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base	Bluetooth & WiFi enabled, dual zone refrigeration or freezing, detachable/reversible lids, interior lights, drain plugs, CFX3 VMSO^3 electronics, USB port, TFT LCD display (dimmable), 3-stage battery protection, anti-condensation heating, 4 x M6 nutserts in base
Scope of delivery	DC and AC connection cables, removable wire basket, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 2 x removable wire baskets, spring-loaded carrying handles, ice maker housing with lid, 2 x ice trays with lid	DC and AC connection cables, 3 x removable wire baskets, spring-loaded carrying handles	DC and AC connection cables, 3 x removable wire baskets, spring-loaded carrying handles
Ref No.	9600025299	9600025300	9600025301	9600025302	9600025303	9600025304