



ENGEL PRODUCT FILE – Generators R2000IS

October 2021

Head Office 1300 436 435



**PRODUCT NAME: R2000IS
2kW Generator**

SUPPLIER:	ENGEL
Long description/ product summary:	<p>R2000iS: 2kW Pure Sinewave Generator</p> <p>This unit boasts world class quality at an affordable price. Comprising all the features you expect in a generator today with the peace of mind that comes from owning an Engel Product. Backed by Engel's no fuss 4 year warranty and supported by a network of service agents nationally you have years of trouble free operation ahead.</p>
Key Features and Benefits:	<ul style="list-style-type: none"> • Compact: Portable and Easy to Handle • 100% Pure Sine Wave • 15 amp Outlet • Encased in Tough material • Powerful 4 Stroke Engine • Super Quiet: 68Db@7m • 7 Hours Continuous Running Time (50% Capacity) • 4.8 Liter Fuel Capacity • Easy Pull Start
Top 5 Selling Points:	<ul style="list-style-type: none"> • Inverter Generators by Engel adopt the latest in design simplicity. It is portable and lightweight with low noise levels. • Our inverter generators feature a super heavy duty engine for long term durability and performance. • Compact and powerful • Four Year Warranty • Australia wide service network

<p>Engine:</p>	<table> <tr> <td>Type</td> <td>R80-i 25° Single cylinder, 4 stroke, air-cooled, cylinder centre inclined</td> </tr> <tr> <td>Displacement</td> <td>79.7cc</td> </tr> <tr> <td>Starting system</td> <td>Recoil start</td> </tr> <tr> <td>Stopping system</td> <td>Ignition primary circuit ground</td> </tr> <tr> <td>Ignition system</td> <td>Transistorized magneto</td> </tr> <tr> <td>Fuel tank capacity (litres)</td> <td>4.8L</td> </tr> <tr> <td>Fuel consumption</td> <td>≤450g/kW.h</td> </tr> <tr> <td>Full load continuous running time</td> <td>4.5h</td> </tr> <tr> <td>Continuous operating hours (50% of rated load)</td> <td>7h</td> </tr> <tr> <td>Oil Capacity</td> <td>0.38L</td> </tr> <tr> <td>Oil alert</td> <td>Yes</td> </tr> <tr> <td>Fuel Cut Solenoid</td> <td>No</td> </tr> <tr> <td>Auto Throttle</td> <td>Eco throttle</td> </tr> <tr> <td>Auto Choke</td> <td>No</td> </tr> <tr> <td>Large Capacity Air Cleaner</td> <td>Yes</td> </tr> <tr> <td>Large Capacity Fuel Tank</td> <td>Yes</td> </tr> <tr> <td>Large Capacity Muffler</td> <td>Yes</td> </tr> <tr> <td>Pilot Lamp</td> <td>Yes</td> </tr> <tr> <td>Air Cleaner</td> <td>Foam Type</td> </tr> <tr> <td>Noise (at 7m)</td> <td>68dBA</td> </tr> </table>	Type	R80-i 25° Single cylinder, 4 stroke, air-cooled, cylinder centre inclined	Displacement	79.7cc	Starting system	Recoil start	Stopping system	Ignition primary circuit ground	Ignition system	Transistorized magneto	Fuel tank capacity (litres)	4.8L	Fuel consumption	≤450g/kW.h	Full load continuous running time	4.5h	Continuous operating hours (50% of rated load)	7h	Oil Capacity	0.38L	Oil alert	Yes	Fuel Cut Solenoid	No	Auto Throttle	Eco throttle	Auto Choke	No	Large Capacity Air Cleaner	Yes	Large Capacity Fuel Tank	Yes	Large Capacity Muffler	Yes	Pilot Lamp	Yes	Air Cleaner	Foam Type	Noise (at 7m)	68dBA				
Type	R80-i 25° Single cylinder, 4 stroke, air-cooled, cylinder centre inclined																																												
Displacement	79.7cc																																												
Starting system	Recoil start																																												
Stopping system	Ignition primary circuit ground																																												
Ignition system	Transistorized magneto																																												
Fuel tank capacity (litres)	4.8L																																												
Fuel consumption	≤450g/kW.h																																												
Full load continuous running time	4.5h																																												
Continuous operating hours (50% of rated load)	7h																																												
Oil Capacity	0.38L																																												
Oil alert	Yes																																												
Fuel Cut Solenoid	No																																												
Auto Throttle	Eco throttle																																												
Auto Choke	No																																												
Large Capacity Air Cleaner	Yes																																												
Large Capacity Fuel Tank	Yes																																												
Large Capacity Muffler	Yes																																												
Pilot Lamp	Yes																																												
Air Cleaner	Foam Type																																												
Noise (at 7m)	68dBA																																												
<p>Generator:</p>	<table> <tr> <td>Rated power output (KVA)</td> <td>1.8kVA</td> </tr> <tr> <td>Max. power output (KVA)</td> <td>1.9kVA</td> </tr> <tr> <td>Rated output frequency</td> <td>50Hz</td> </tr> <tr> <td>Rated output voltage</td> <td>230V</td> </tr> <tr> <td>DC Output No</td> <td>No</td> </tr> <tr> <td>USB (DC Output)</td> <td>1A 5V / 2.1A 5V</td> </tr> <tr> <td>AC Output</td> <td>240V 50HZ</td> </tr> <tr> <td>Battery Charging</td> <td>No</td> </tr> <tr> <td>Frequency Meter</td> <td>Yes</td> </tr> <tr> <td>Voltmeter</td> <td>Yes</td> </tr> <tr> <td>Generator Type</td> <td>Multipole field rotation type (Inverter)</td> </tr> <tr> <td>Rated Voltage</td> <td>240V</td> </tr> <tr> <td>Rated Frequency</td> <td>50HZ</td> </tr> <tr> <td>Fuel Gauge</td> <td>yes</td> </tr> <tr> <td>AC Circuit Breaker</td> <td>No</td> </tr> <tr> <td>DC Circuit Breaker</td> <td>No</td> </tr> <tr> <td>Parallel operations connection ports</td> <td>yes</td> </tr> <tr> <td>Parallel operations connection cable</td> <td>Optional</td> </tr> <tr> <td>4 wheel dolly kit</td> <td>No</td> </tr> <tr> <td>Condition</td> <td>With eco-throttle Switched on within 3/4 output</td> </tr> <tr> <td>THD at FULL LOAD</td> <td>≤3%</td> </tr> <tr> <td>Lifetime</td> <td>500H</td> </tr> </table>	Rated power output (KVA)	1.8kVA	Max. power output (KVA)	1.9kVA	Rated output frequency	50Hz	Rated output voltage	230V	DC Output No	No	USB (DC Output)	1A 5V / 2.1A 5V	AC Output	240V 50HZ	Battery Charging	No	Frequency Meter	Yes	Voltmeter	Yes	Generator Type	Multipole field rotation type (Inverter)	Rated Voltage	240V	Rated Frequency	50HZ	Fuel Gauge	yes	AC Circuit Breaker	No	DC Circuit Breaker	No	Parallel operations connection ports	yes	Parallel operations connection cable	Optional	4 wheel dolly kit	No	Condition	With eco-throttle Switched on within 3/4 output	THD at FULL LOAD	≤3%	Lifetime	500H
Rated power output (KVA)	1.8kVA																																												
Max. power output (KVA)	1.9kVA																																												
Rated output frequency	50Hz																																												
Rated output voltage	230V																																												
DC Output No	No																																												
USB (DC Output)	1A 5V / 2.1A 5V																																												
AC Output	240V 50HZ																																												
Battery Charging	No																																												
Frequency Meter	Yes																																												
Voltmeter	Yes																																												
Generator Type	Multipole field rotation type (Inverter)																																												
Rated Voltage	240V																																												
Rated Frequency	50HZ																																												
Fuel Gauge	yes																																												
AC Circuit Breaker	No																																												
DC Circuit Breaker	No																																												
Parallel operations connection ports	yes																																												
Parallel operations connection cable	Optional																																												
4 wheel dolly kit	No																																												
Condition	With eco-throttle Switched on within 3/4 output																																												
THD at FULL LOAD	≤3%																																												
Lifetime	500H																																												



3

Physical:	<table> <tr> <td>Dimensions (mm)</td> <td>498 × 312 × 467</td> </tr> <tr> <td>Weight</td> <td>22kg</td> </tr> <tr> <td>Packing</td> <td>Carton</td> </tr> <tr> <td>Packing Size (mm)</td> <td>520 × 320 × 490</td> </tr> </table>	Dimensions (mm)	498 × 312 × 467	Weight	22kg	Packing	Carton	Packing Size (mm)	520 × 320 × 490				
Dimensions (mm)	498 × 312 × 467												
Weight	22kg												
Packing	Carton												
Packing Size (mm)	520 × 320 × 490												
Parts Available:													
Available accessories:	<table> <tr> <td>ENGPARKIT</td> <td>Parallel Kit</td> </tr> <tr> <td>ENGSK2000</td> <td>Service Kit</td> </tr> <tr> <td>Service Kit includes</td> <td>1 x Oil transfer pump</td> </tr> <tr> <td></td> <td>1 x 1 litre oil (15W-40)</td> </tr> <tr> <td></td> <td>1 x Spark plug to suit</td> </tr> <tr> <td></td> <td>1 x Complete air cleaner to suit</td> </tr> </table>	ENGPARKIT	Parallel Kit	ENGSK2000	Service Kit	Service Kit includes	1 x Oil transfer pump		1 x 1 litre oil (15W-40)		1 x Spark plug to suit		1 x Complete air cleaner to suit
ENGPARKIT	Parallel Kit												
ENGSK2000	Service Kit												
Service Kit includes	1 x Oil transfer pump												
	1 x 1 litre oil (15W-40)												
	1 x Spark plug to suit												
	1 x Complete air cleaner to suit												