

EcoFlow DELTA 2 is a must-have for any home that puts power security & comfort first. Ensure you're prepared with the power station made for almost any situation your family could find themselves in. All while staying green.

1024Wh-3040Wh expandable capacity

DELTA 2 offers a large 1024Wh battery capacity, expandable to 2048Wh with the DELTA 2 Extra Battery or 3040Wh with the DELTA Max Extra Battery. Keep your appliances running for daily use or as home backup.

1800W AC Output with 13 outlets

DELTA 2's output of 1800W handles 90% of electronics and powers 13 devices simultaneously. No fears of overloading for high-wattage devices (up to 2400W) with X-Boost technology.

Incredible fast charging

Fastest AC charging with X-Stream technology: charge 0-80% in 50 mins and 0-100% in 80 mins. Charge from solar in 3-6 hours with 500W solar input. Always prepared for a power outage or take a last-minute camping trip.

Longest-lasting and safe LFP battery

The DELTA 2 is powered by premium LFP batteries with 3000X life cycles, which is 6X longer than the industry's average. It's long-lasting, stable and durable.





(10W)



(40W)

CPAP

(40W)







(1300W)

0.6 Hours





(11Wh)

89 Charges





(16Wh)

60 Charges



25 Charges





(65W)

(60W)

16-32 Hours









16 Charges





0.7 Hours



0.7 Hours



(1260W)

0.6 Hours





0.6 Hours



through creative, environmentally-conscious innovation.

ECOFLOW

EcoFlow is an eco-friendly energy solutions company. Since its founding in 2017,

EcoFlow has provided peace of mind to customers in over 100 markets through its DELTA and RIVER portable power stations and varied accessories. EcoFlow's mission is to reinvent the way the world generates, stores and uses energy

Email: sales@ecoflow.com



Specification

DELTA 2

Model Name	DELTA 2
Capacity	1024 Wh
Extra Battery	DELTA 2 Extra Battery: 1024 Wh DELTA Max Extra Battery: 2016 Wh

OUTPUT

AC Output (x4)	4 outlets, 1800W total (Surge 2700W), X-Boost 2400W
USB-A Output (x2)	5V, 2.4A, 12W Max
USB-A Fast Charge (x2)	5V, 2.4A / 9V, 2A / 12V, 1.5A, 18W Max
USB-C Output (x2)	5/9/12/15/20V, 5A, 100W Max
Car Power Output (x1)	12.6V, 10A, 126W Max
DC5521 Output (x2)	12.6V, 3A

INPUT

AC Charging	1200W
Solar Charging	500W Max, 11-60V, 15A
Car Charging	Supports 12V/24V Battery, default 8A

BATTERY

Battery Chemistry	LFP (LiFePO4 battery)
Cycle Life	3000 cycles to 80%+ capacity

Connectivity	Wi-Fi & Bluetooth	
Dimension	15.7 × 8.3 × 11 in / 400 × 211 × 281 mm	
Weight	27 lbs / 12 kg	
What's in the box	DELTA 2, AC charging cable, car charging cable, DC5521 DC5525 cable, user manual, app quick start guide, warranty ca	

CHARGING TIME

OTIANOINO TIME	
AC Wall Outlet	0-80% in 50min, 0-100% in 80min (1200W Max)
Smart Generator	0-80% in 50min, 0-100% in 80min (1100W Max)
Portable Solar Panel	3-6 Hours (1*400W / 2*220W)
Car Charger	11 Hours (96W)





DELTA 2 Solar Generators

Portable Solar Panels		Recharge Time
110W	2 Sets	6-12 hrs
TIOVV	4 Sets	3-6 hrs (2 series 2parallel)
160W	1 Set	8-16 hrs
100 00	2 Sets	4-8 hrs
220W	1 Set	6-12 hrs
220W	2 Sets	3-6 hrs
400W	1 Set	3-6 hrs

ECOFLOW

Power a New World

