



SLZC12V7 12/24V AC Battery Charger 7A

SPECIFICATION / TECHNICAL SHEET

Specifications		
Input Voltage		220-240V AC
Input Power		150W max
Output Voltage		12/24V DC
IP Rating		IP65
Dimensions	Length	148mm (± 0.5mm)
	Width	84mm (± 0.5mm)
	Depth	47mm (± 0.5mm)
Characteristics		
Output Current	12V Lead-Acid Normal Mode	7A±10%
	24V Lead-Acid Normal Mode	3.5A±10%
	12V Lithium Mode	7A±10%
	12V AGM Mode	7A±10%
	24V AGM Mode	3.5A±10%
	12V Supply Mode	5A±10%
	12V Repair Mode	1.5A±0.5A
	12V Maintain Mode	5A±10%
Constant Voltage	12V Lead-Acid Normal Mode	14.4V±0.25V
	24V Lead-Acid Normal Mode	28.8V±0.5V
	12V Lithium Mode	14.5V±0.25V
	12V AGM Mode	14.7V±0.25V
	24V AGM Mode	29.4V±0.5V
	12V Supply Mode	13.6V±0.5V
	12V Repair Mode	16.5V±0.5V
	12V Maintain Mode	13.6V±0.5V
Battery Chemistries	12V/24V Lead-Acid Battery	(Wet, Gel, SLA, AGM),
	12V Lithium	(LiFePO4)
	Operating Temperature	0°C ~ 40°C
	Storage Temperature	-20°C ~ 60°C
	Warranty	2 Years



Features

- Sealed IP65 Case
- Lithium Mode With Wake Up Function
- Suitable For Lead Batteries (Wet, Gel, SLA, AGM)
- Easy To Use Settings
- Supply, Repair & Maintain Modes
- Memory Function
- Passive Cooling
- 2 Year Warranty